(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization International Bureau



(43) International Publication Date 28 April 2005 (28.04.2005)

PCT

(10) International Publication Number WO 2005/038934 A1

(51) International Patent Classification7:

H01L 31/04

(21) International Application Number:

PCT/JP2004/015658

(22) International Filing Date: 15 October 2004 (15.10.2004)

(25) Filing Language:

(26) Publication Language:

English

(30) Priority Data: 2003-357778

17 October 2003 (17.10.2003) JP

(71) Applicant (for all designated States except US): CANON KABUSHIKI KAISHA [JP/JP]; 3-30-2, Shimomaruko, Ohta-ku, Tokyo 146-8501 (JP).

(72) Inventor; and

 $(\dot{})$

- (75) Inventor/Applicant (for US only): TAKEYAMA, Yoshifumi [JP/JP]; c/o Canon Kabushiki Kaisha, 3-30-2, Shimomaruko, Ohta-ku, Tokyo 146-8501 (JP).
- (74) Agents: OKABE, Masao et al.; No. 602, Fuji Bldg., 2-3, Marunouchi 3-chome, Chiyoda-ku, Tokyo 100-0005 (JP).

- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).


Published:


100

- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

[Continued on next page]

(54) Title: PHOTOVOLTAIC ELEMENT AND METHOD OF PRODUCING PHOTOVOLTAIC ELEMENT





(57) Abstract: A photovoltaic element is provided which has at least a photovoltaic layer and a transparent electrode layer deposited on a metal substrate, a portion of the transparent electrode layer being continuously removed at a peripheral part of the metal substrate, wherein an island-shaped transparent-electrode-layer-removed-portion is provided in the transparent electrode layer in a power-generating region surrounded by the removed portion of the transparent electrode layer, a rear surface side bus-bar electrode electrically connected to the metal substrate is disposed on the rear surface side of the metal substrate at the rear of the island-shaped transparent-electrode-layer-removed-portion, and the rear surface side bus-bar electrode is connected to the metal substrate at a portion corresponding to the island-shaped transparent-electrode-layer-removed-portion, and which can enhance the degree of freedom for the shape of a photovoltaic element module while ensuring the reliability of the photovoltaic element.